

# 400 SERIES















## COMPONENT LIST











The LOC-A-BLOC System of engineered decorative walls, has a full range of structural components, all with matching face finishes.





For technical details, please either consult the LOC-A-BLOC design manual, view our website on [www.locabloc.com.au](http://www.locabloc.com.au) or discuss your specific needs with a Company representative by phoning 1800 027 070.

<b>STANDARD BLOCK COMPONENTS</b>			
<b>Component Part Number</b>	<b>Diagram (Not to Scale)</b>	<b>Description</b>	<b>Approx Weight (Kg)</b>
400 SSS		Single side bolstered standard component 400 x 200 x 200 mm. 12.5 units / square face metre.	27
405 HSS		Single side bolstered standard half block component. 200 x 200 x 200 mm	15
400 CSS		Single side bolstered corner component. Front and one end bolstered.	26
405 HCS		Single side bolstered half corner component. Front and one end bolstered. 200 x 200 x 200 mm.	17
445 SSS		Single side bolstered angle component. Used to attain a 45° angle. 400 (on face) x 200 x 200 mm.	25
445 HSS		Single side bolstered half angle component 200 [on face] x 200 x 200mm	9
400 SSC		Standard component for convex walls with radii of 2 m. or more. 400 (on face) x 200 x 200 mm.	27
400 SDS		Double side bolstered standard component. 400 x 200 x 200 mm. 12.5 units / square face metre.	30

Component Part Number	Diagram (Not to Scale)	Description	Approx Weight (Kg)
405 HDS		Double side bolstered half component. 200 x 200 x 200 mm.	17
400 CUD		Double side bolstered universal corner component. 400 x 200 x 200 mm.	26
400 CIS		Single side bolstered internal corner component. 400 x 200 x 200 mm.	24
400 EDS		Double side bolstered component. 400 x 200 x 200 mm.	30
405 HDE		Double side bolstered standard half end component. 200 x 200 x 200 mm.	18
400 SFF		Standard component with flat facing suitable for signage. 400 x 200 x 200 mm.	26
405 HFF		Half standard component with flat facing suitable for signage 200 x 200 x 200mm	15
400 SNF		Standard blank component without facing. 400 x 200 x 200 mm.	24
405 HNF		Standard blank half component without facing 200 x 200 x 200mm	12
400 NFC		No face convex component 400 [ on face ] x 200 x 200mm	24
400 RSS		As for 400 SSS with 50mm dia. relief pipe. Approximately every third or fourth unit in run.	26
400 RNS		As for 400SNF with 50mm dia. relief pipe. Approximately every third or fourth unit in run.	23
400 RSC		As for 400SSC with 50mm dia. relief pipe. Approximately every third or fourth unit in run.	26
400 RNC		As for 400NFC with 50mm dia. relief pipe. Approximately every third or fourth unit in run.	23

## DRY MIX COMPONENTS

Component Part Number	Diagram (Not to Scale)	Description	Approx Weight (Kg)
400 NSV		Bolstered veneer used to match Loc-A-Bloc structures with existing walls. 400 x 200 x 35 mm.	3
400 SPB		Pier block bolstered on all four sides. 400 x 400 x 200 mm.	60
400 SPC		Standard pyramid cap for use with the pier block. 460 x 460 x 35/90 mm.	22
400 SAC		Standard apex cap. 400 x 260 x 35/85 mm.	11
480 SBC		Single bolstered edge capping. 600 x 280 x 80 mm.	23
480 DBC		Double bolstered edge capping. 600 x 280 x 80 mm.	20
480 SRC		Single rounded edge capping incorporating drip moulds. 600 x 280 x 80 mm.	22
480 DRC		Double rounded edge capping incorporating drip moulds. 600 x 280 x 80 mm.	22

<b>SINGLE POUR WALL COMPONENTS</b>			
<b>Component Part Number</b>	<b>Diagram (Not to Scale)</b>	<b>Description</b>	<b>Approx Weight (Kg)</b>
400 FNS		No face standard footing component 400 x 200 x 200mm with 45mm cut out of two back corners	23
400 FSS		Single side standard footing component 400 x 200 x 200mm with 45mm cut out of two back corners	26
400 FNC		No face convex footing component 400 [on face] x 200 x 200mm with 45mm cut out of two back corners	23
400 FSC		Single side convex footing component 400 [on face] x 200 x 200mm with 45mm cut out of two back corners	26

**COLOURS:**

LOC-A-BLOC System products are manufactured to simulate natural materials and are generally available in a mixture of light and dark sandstone blend. Please note that some variation may occur between batches.

Other colours available are simulated basalt, or bluestone grade.

**PACKING:**

All components are packed on standard non-returnable pallets.

Series 400 standard blocks are packed 60 per pallet.

Varying quantities of accessories - depending on type - are packed on pallets.

**DELIVERY:**

There is no delivery charge for deliveries on orders of five pallets or more within the Greater Sydney area including the Blue Mountains, Central coast and Newcastle area. Orders of four pallets or less within the above region will attract a delivery fee.

For deliveries outside the area a delivery charge will be negotiated at time of order placement.

A repackaging fee will be charged for all entered / picked orders that are changed [By the Customer / Contractor] within 2 working days of the agreed dispatch date. The actual dispatch date may also vary and these variations will be advised at the time of the change.